

# MEDI+RANGE UNDERCOUNTER CABINET WMP135



WMP135

Dimensions (mm)	External	Internal
Width	606	536
Depth	577	434
Height	805	606
Door Opening		606
<b>Capacity</b>		
Capacity cu.ft/ltrs	4.8/135	

## KEY FEATURES

- Stainless steel exterior and aluminium interior
- Barrel locked doors
- Interior LED lighting
- Magnetic balloon door gaskets with 100% tight seal
- White nylon coating wire shelves
- Precision injected, high density polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Pilaster racking with removable shelving clips
- Front vented refrigeration system
- Designed and engineered to operate efficiently up to 32°C ambient
- Air cooled condensing unit
- Defrost water is vaporised using recycled heat from compressor
- High performance helium leak testing
- Glass or solid door models

## MEDI+ CONTROLLER

- Clear digital display
- Audio and visual hi/lo temp alarm
- Audio and visual door open alarm
- Maximum and minimum temperature memory
- Auto defrost
- Air & evaporator probe
- Lockable keypad
- Condenser cleaning warning to ensure optimum performance is maintained
- Volt free alarm contacts for connecting to supervisory or BMS system
- Modbus network data connection for comprehensive monitoring of temperatures, alarms and defrost via 3rd party supervisory system
- Precise temperature control using decimal point operation

## OPTIONS

- Punched stainless steel shelves
- Additional shelving
- Left hand door hang
- Mains failure alarm



# MEDI+ RANGE UNDERCOUNTER CABINET WMP135

HWMP135	
Temperature (°C)	+2 / +8°C
Climate Class	Class 4 (30°C)
Power Supply	230V/50Hz/1Ph
Fuse (Amps)	13
Defrost	Automatic Off Cycle
Noise level (dBA)	55

### Fittings

White nylon coated wire shelves	2
---------------------------------	---

### Electrical / Energy Data

Refrigerant	R600a
Start Up (Amps)	3.7
Running (Amps)	0.53
Heat Rejection *	194

### IMPORTANT NOTES:

\*Heat rejection is evaporating at -10°C in 32°C Ambient  
 All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration  
 Bryggen Road,  
 North Lynn Industrial Estate  
 King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000  
 Spares: +44(0) 1553 817 017  
 E info@williams-refrigeration.co.uk  
 W www.williams-refrigeration.co.uk

