

MEDI+RANGE BOTTOM MOUNTED CABINETS WMP410/WMP523



WMP410



WMP523

Dimensions (mm)	External	Internal	External	Internal
Width	695	545	727	567
Depth	684	477	837	660
Height	1956	1315	1940	1332
Door Opening		545		567
Capacity	14.5/410		18.5/523	

KEY FEATURES

- 523 models - stainless steel exterior & interior
- 410 models - stainless steel exterior & aluminium interior
- Full length integral 'easy grab' door handle
- Interior LED lighting
- Self closing doors
- Anti-tilt trayslides (shelf support)
- Removable racking system
- Barrel locked doors
- Heavy duty, non-marking, swivel castors with brakes
- Magnetic balloon door gaskets with 100% tight seal
- White nylon coating wire shelves
- Precision injected, high density 80mm polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Defrost water is vaporised using recycled heat from compressor
- Designed and engineered to operate efficiently up to 43°C ambient
- High performance helium leak testing
- Air cooled condensing unit
- Glass door (H models only)

MEDI+ CONTROLLER

- Clear digital display
- Audio and visual hi/lo temp alarm
- Audio and visual door open alarm
- Maximum and minimum temperature memory
- Auto defrost
- Air & evaporator probe
- Lockable keypad
- Condenser cleaning warning to ensure optimum performance is maintained
- Volt free alarm contacts for connecting to supervisory or BMS system
- Modbus network data connection for comprehensive monitoring of temperatures, alarms and defrost via 3rd party supervisory system
- Precise temperature control using decimal point operation

OPTIONS

- Punched stainless steel shelves
- Additional shelving
- Left hand door hang
- Mains failure alarm



MEDI+RANGE BOTTOM MOUNTED CABINETS WMP410/WMP523

	HWMP410	HWMP523	LWMP523
Temperature (°C)	+2 / +8°C	+2 / +8°C	-18 / -22°C
Climate Class	Class 5	Class 5	Class 5
Power Supply	230V/50Hz/1Ph		
Fuse (Amps)	13	13	13
Defrost	Automatic Off Cycle	Automatic Off Electric	Automatic Electric
Noise level (dBA)	63	63	61

Fittings

White nylon coated wire shelves	4	4	4
---------------------------------	---	---	---

Electrical / Energy Data

Refrigerant	R290	R290	R290
Start Up (Amps)	9.5	9.5	9.5
Running (Amps)	1.75	1.67	2.59
Heat Rejection*	484	484	623

IMPORTANT NOTES:

*Heat rejection is evaporating at -10°C in 32°C Ambient
 All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
 Bryggen Road,
 North Lynn Industrial Estate
 King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
 Spares: +44(0) 1553 817 017
 E info@williams-refrigeration.co.uk
 W www.williams-refrigeration.co.uk

