

MEDI+RANGE TOP MOUNTED CABINETS WMP620/WMP1295



WMP620



WMP1295

| Dimensions (mm) | External | Internal | External | Internal |
|---------------------|----------|----------|-----------|----------|
| Width | 727 | 567 | 1400 | 1240 |
| Depth | 824 | 665 | 854 | 665 |
| Height | 1960 | 1411 | 1960 | 1411 |
| Door Opening | | 567 | | 567 |
| Capacity | | | | |
| Capacity cu.ft/ltrs | 21.9/620 | | 45.7/1295 | |

KEY FEATURES

- Stainless steel exterior and aluminium interior
- Full length integral 'easy grab' door handle
- Self closing doors
- Interior LED lighting
- Anti-tilt trayslides (shelf support)
- Removable racking system
- Barrel locked doors
- Heavy duty, non-marking, swivel castors with brakes
- Magnetic balloon door gaskets with 100% tight seal
- White nylon coating wire shelves
- 80mm precision injected, high density polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Defrost water is vaporised using recycled heat from compressor
- Designed and engineered to operate efficiently up to 43°C ambient
- High performance helium leak testing
- Air cooled condensing unit
- Glass door (H models only)

MEDI+ CONTROLLER

- Clear digital display
- Audio and visual hi/lo temp alarm
- Audio and visual door open alarm
- Maximum and minimum temperature memory
- Auto defrost
- Air & evaporator probe
- Lockable keypad
- Condenser cleaning warning to ensure optimum performance is maintained
- Volt free alarm contacts for connecting to supervisory or BMS system
- Modbus network data connection for comprehensive monitoring of temperatures, alarms and defrost via 3rd party supervisory system
- Precise temperature control using decimal point operation

OPTIONS

- Punched stainless steel shelves
- Additional shelving
- Left hand door hang
- Mains failure alarm



MEDI+RANGE TOP MOUNTED CABINETS WMP620/WMP1295

| | HWMP620 | LWMP620 | HWMP1295 | LWMP1295 |
|-------------------|---------------------|--------------------|------------------------|--------------------|
| Temperature (°C) | +2 / +8°C | -18 / -22°C | +2 / +8°C | -18 / -22°C |
| Climate Class | Class 5 | Class 5 | Class 5 | Class 5 |
| Power Supply | 230V/50Hz/1Ph | | | |
| Fuse (Amps) | 13 | 13 | 13 | 13 |
| Defrost | Automatic Off Cycle | Automatic Electric | Automatic Off Electric | Automatic Electric |
| Noise level (dBA) | 63 | 63 | 65 | 70 |

Fittings

| | | | | |
|---------------------------------|---|---|---|---|
| White nylon coated wire shelves | 4 | 4 | 8 | 8 |
|---------------------------------|---|---|---|---|

Electrical / Energy Data

| | | | | |
|-----------------|------|------|------|------|
| Refrigerant | R290 | R290 | R290 | R290 |
| Start Up (Amps) | 9.5 | 14.2 | 13.5 | 13.5 |
| Running (Amps) | 1.64 | 3.63 | 1.42 | 3.63 |
| Heat Rejection* | 484 | 623 | 768 | 1068 |

IMPORTANT NOTES:

*Heat rejection is evaporating at -10°C in 32°C Ambient
All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

