

Pharmacy Refrigerator

— **HYC-610**



Ergonomic Design



LED Temperature Display

- Display precision 0.1°C.



Multiple Alarm Functions

- Alarms including high and low temperature, remote alarm, sensor error, power failure, low battery, door ajar.



Adjustable Shelves

- The shelves are adjustable to any height to fulfill different user requirements.



Large Storage Space



Lockable Design



Self Closing Door with 90° Stay Open Feature

Qingdao Haier Biomedical Co.,Ltd.

No.280 Feng Yuan Road, High-tech Zone,
Qingdao, 266109, P.R. China
Tel: +86-0532-88935955
Website: www.haiermedical.com



Haier Biomedical
International



Haier Biomedical
International



@haiermedicalint



@haierbiomedicalint



Haier Biomedical
International

Intelligent Reagent Refrigerator

— HYC-610

Product Advantages



Energy Efficient Hydrocarbon (HC) Refrigeration System

Imported efficient inverter compressor with optimized cooling system, more energy efficient.



Greener by Design

Hydrocarbon compressor and refrigerant, the refrigerant does not contain any fluorine or chlorine, greener and environmentally friendly.



Energy conserving, maintains temperature uniformity to protect valuable samples.



Superior cabinet temperature uniformity, automatic defrosting

The distribution point for performance tests in the cabinet increased from 2 to 9 points.



HYC-610

Specifications

Model	HYC-610			
Technical Data	Cabinet Type	Upright, single door	Upright, single door	
	Climate Class	ST	ST	
	Cooling Type	Forced air cooling	Forced air cooling	
	Defrost Mode	Auto	Auto	
	Refrigerant	HC	HC	
	Noise((dB(A))	43	43	
Performance	Temp Range(°C)	2-8	2-8	
Control	Controller	Microprocessor	Microprocessor	
	Display	LED	LED	
Electrical Data	Power Supply(V/Hz)	220-240/50&60	115/60	
	Power(W)	550	500	
	Electrical Current(A)	3	6.2	
Alarms	High/Low Temp	Y	Y	
	Remote System	Y	Y	
	Power Failure	Y	Y	
	Sensor Error	Y	Y	
	Low Battery	Y	Y	
	Door Ajar	Y	Y	
Accessories	Caster	Y	Y	
	Foot	Y	Y	
	Porthole	Y	Y	
	Shelves/Basket	6/-	6/-	
	Temperature Recorder	Optional	Optional	
	USB Interface	Optional	Optional	
Dimensions	Capacity(L/Cu.Ft)	610/21.6	610/21.6	
	Net/Gross Weight(approx)	kg	204/227	204/227
		lbs	449.7/500.4	449.7/500.4
	Interior Dimensions(W*D*H)	mm	680*640*1400	680*640*1400
		in	26.8*25.2*55.1	26.8*25.2*55.1
	Exterior Dimensions(W*D*H)	mm	780*840*1945	780*840*1945
		in	30.7*33.1*76.6	30.7*33.1*76.6
	Packing Dimensions(W*D*H)	mm	865*945*2090	865*945*2090
in		34.1*37.2*82.3	34.1*37.2*82.3	
Others	Container Load(20'/40'/40'H)	12/26/26	12/26/26	
	Certificate	CE	UL	